

# STARPOWER

SEMICONDUCTOR

# MOSFET

## MD120HFR120C2S

**1200V/120A 2 in one-package**

### General Description

STARPOWER MOSFET Power Module provides very low  $R_{DS(on)}$  as well as optimized intrinsic diode. It's designed for the applications such SMPS and DC drives.

### Features


- SiC power MOSFET
- Low  $R_{DS(on)}$
- Optimized intrinsic reverse diode
- Chip sintering technology
- Low inductance case avoid oscillations
- Isolated copper baseplate using DBC technology



### Typical Applications

- Main and auxiliary AC drives of electric vehicles
- DC servo and robot drives
- Battery vehicles
- UPS equipment
- Plasma cutting

### Equivalent Circuit Schematic



**Absolute Maximum Ratings****MOSFET**

Symbol	Description	Value	Unit
$V_{DSS}$	Drain-Source Voltage	1200	V
$V_{GSS}$	Gate-Source Voltage	$\pm 20$	V
$I_D$	Drain Current @ $T_C=25^\circ\text{C}$ @ $T_C=120^\circ\text{C}$	200	A
		120	A
$I_{DM}$	Pulsed Drain Current	548	A

**Inverse Diode**

Symbol	Description	Value	Unit
$I_S$	Source Current	120	A
$I_{SM}$	Pulsed Source Current	548	A

**Module**

Symbol	Description	Value	Unit
$T_{jmax}$	Maximum Junction Temperature	175	$^\circ\text{C}$
$T_{jop}$	Operating Junction Temperature	-40 to +150	$^\circ\text{C}$
$T_{STG}$	Storage Temperature Range	-40 to +125	$^\circ\text{C}$
$V_{ISO}$	Isolation Voltage RMS, $f=50\text{Hz}, t=1\text{min}$	4000	V

**MOSFET Characteristics**

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$R_{DS(on)}$	Static Drain-Source On-Resistance	$I_D=80A, V_{GS}=18V,$ $T_j=25^\circ C$		10	13	m $\Omega$
		$I_D=80A, V_{GS}=18V,$ $T_j=125^\circ C$		15		
$V_{GS(th)}$	Gate-Source Threshold Voltage	$I_D=40mA, V_{DS}=V_{GS},$ $T_j=25^\circ C$	2.7		5.6	V
$g_{fs}$	Forward Transconductance	$V_{DS}=10V, I_D=80A$		33.2		S
$I_{DSS}$	Drain-Source Leakage Current	$V_{DS}=V_{DSS}, V_{GS}=0V,$ $T_j=25^\circ C$			40	$\mu A$
$I_{GSS}$	Gate-Source Leakage Current	$V_{GS}=V_{GSS}, V_{DS}=0V,$ $T_j=25^\circ C$			0.4	$\mu A$
$C_{iss}$	Input Capacitance	$V_{GS}=0V, V_{DS}=800V,$ $f=1MHz$		5.35		nF
$C_{oss}$	Output Capacitance			0.30		nF
$C_{rss}$	Reverse Transfer Capacitance			0.11		nF
$Q_g$	Total Gate Charge			428		nC
$Q_{gs}$	Gate-Source Charge	$I_D=80A, V_{DS}=600V,$ $V_{GS}=18V$		88		nC
$Q_{gd}$	Gate-Drain ("Miller") Charge			164		nC
$t_{d(on)}$	Turn-On Delay Time	$V_{DS}=400V, I_D=72A,$ $R_G=0\Omega, V_{GS}=18V,$ $T_j=25^\circ C$		21		ns
$t_r$	Rise Time			39		ns
$t_{d(off)}$	Turn-Off Delay Time			49		ns
$t_f$	Fall Time			24		ns
$E_{on}$	Turn-On Switching Loss	$V_{DS}=600V, I_D=80A,$ $R_G=0\Omega, V_{GS}=18V,$ $T_j=25^\circ C$		1.13		mJ
$E_{off}$	Turn-Off Switching Loss			0.47		mJ


**Inverse Diode Characteristics**

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$V_{SD}$	Diode Forward Voltage	$I_S=80A, V_{GS}=0V, T_j=25^\circ C$		3.2		V
$t_{rr}$	Diode Reverse Recovery Time	$V_R=600V, I_S=80A,$ $-di/dt=8800A/\mu s, T_j=25^\circ C$		25		ns
$Q_r$	Diode Reverse Recovery Charge			0.46		$\mu C$
$I_{RM}$	Peak Reverse Recovery Current			36		A

**Module Characteristics**  $T_c=25^{\circ}\text{C}$  unless otherwise noted


Symbol	Parameter	Min.	Typ.	Max.	Unit
$R_{thJC}$	Junction-to-Case(Mosfet)			0.181	K/W
$R_{thCH}$	Case-to-Heatsink (Mosfet)		0.020		K/W
	Case-to-Heatsink (per Module)		0.010		
M	Terminal Connection Torque, Screw M6	2.5		5.0	N.m
	Mounting Torque, Screw M6	3.0		5.0	
G	Weight of Module		300		g

**Circuit Schematic**



**Package Dimensions**

Dimensions in Millimeters



## Terms and Conditions of Usage

The data contained in this product datasheet is exclusively intended for technically trained staff. you and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application.

This product data sheet is describing the characteristics of this product for which a warranty is granted. Any such warranty is granted exclusively pursuant the terms and conditions of the supply agreement. There will be no guarantee of any kind for the product and its characteristics.

Should you require product information in excess of the data given in this product data sheet or which concerns the specific application of our product, please contact the sales office, which is responsible for you (see [www.powersemi.cc](http://www.powersemi.cc)), For those that are specifically interested we may provide application notes.

Due to technical requirements our product may contain dangerous substances. For information on the types in question please contact the sales office, which is responsible for you.

Should you intend to use the Product in aviation applications, in health or live endangering or life support applications, please notify.

If and to the extent necessary, please forward equivalent notices to your customers.  
Changes of this product data sheet are reserved.