

# STARPOWER

SEMICONDUCTOR

IGBT

## GD75FFU120C6S

**1200V/75A 6 in one-package**

### General Description

STARPOWER IGBT Power Module provides ultra low conduction and switching loss as well as short circuit ruggedness. They are designed for the applications such as general inverters and UPS




### Features

- NPT IGBT technology
- 10 $\mu$ s short circuit capability
- Low switching losses
- $V_{CE(sat)}$  with positive temperature coefficient
- Square RBSOA
- Low inductance case
- Fast & soft reverse recovery anti-parallel FWD

### Typical Applications

- Inverter for motor drive
- AC and DC servo drive amplifier
- Uninterruptible power supply

### Equivalent Circuit Schematic



**Absolute Maximum Ratings**  $T_C=25^{\circ}\text{C}$  unless otherwise noted**IGBT**

Symbol	Description	Values	Unit
$V_{CES}$	Collector-Emitter Voltage	1200	V
$V_{GES}$	Gate-Emitter Voltage	$\pm 20$	V
$I_C$	Collector Current @ $T_C=25^{\circ}\text{C}$	115	A
	@ $T_C=80^{\circ}\text{C}$	75	A
$I_{CM}$	Pulsed Collector Current $t_p=1\text{ms}$	150	A
$P_D$	Maximum Power Dissipation @ $T_j=150^{\circ}\text{C}$	667	W

**Diode**

Symbol	Description	Values	Unit
$V_{RRM}$	Repetitive Peak Reverse Voltage	1200	V
$I_F$	Diode Continuous Forward Current	75	A
$I_{FM}$	Diode Maximum Forward Current $t_p=1\text{ms}$	150	A

**Module**

Symbol	Description	Values	Unit
$T_{jmax}$	Maximum Junction Temperature	150	$^{\circ}\text{C}$
$T_{jop}$	Operating Junction Temperature	-40 to +125	$^{\circ}\text{C}$
$T_{STG}$	Storage Temperature Range	-40 to +125	$^{\circ}\text{C}$
$V_{ISO}$	Isolation Voltage RMS, $f=50\text{Hz}$ , $t=1\text{min}$	4000	V

**IGBT Characteristics**  $T_c=25^\circ\text{C}$  unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage	$I_C=75\text{A}, V_{GE}=15\text{V}, T_j=25^\circ\text{C}$		3.10	3.55	V
		$I_C=75\text{A}, V_{GE}=15\text{V}, T_j=125^\circ\text{C}$		3.45		
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=0.75\text{mA}, V_{CE}=V_{GE}, T_j=25^\circ\text{C}$	4.4	5.2	6.0	V
$I_{CES}$	Collector Cut-Off Current	$V_{CE}=V_{CES}, V_{GE}=0\text{V}, T_j=25^\circ\text{C}$			5.0	mA
$I_{GES}$	Gate-Emitter Leakage Current	$V_{GE}=V_{GES}, V_{CE}=0\text{V}, T_j=25^\circ\text{C}$			400	nA
$R_{Gint}$	Internal Gate Resistance			0		$\Omega$
$C_{ies}$	Input Capacitance	$V_{CE}=30\text{V}, f=1\text{MHz}, V_{GE}=0\text{V}$		6.35		nF
$C_{res}$	Reverse Transfer Capacitance				0.23	
$Q_G$	Gate Charge	$V_{GE}=15\text{V}$		600		nC
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600\text{V}, I_C=75\text{A}, R_G=7.5\Omega, V_{GE}=\pm 15\text{V}, T_j=25^\circ\text{C}$		286		ns
$t_r$	Rise Time			53		ns
$t_{d(off)}$	Turn-Off Delay Time			304		ns
$t_f$	Fall Time			103		ns
$E_{on}$	Turn-On Switching Loss			4.16		mJ
$E_{off}$	Turn-Off Switching Loss			2.17		mJ
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600\text{V}, I_C=75\text{A}, R_G=7.5\Omega, V_{GE}=\pm 15\text{V}, T_j=125^\circ\text{C}$		297		ns
$t_r$	Rise Time			56		ns
$t_{d(off)}$	Turn-Off Delay Time			321		ns
$t_f$	Fall Time			136		ns
$E_{on}$	Turn-On Switching Loss			5.82		mJ
$E_{off}$	Turn-Off Switching Loss			3.44		mJ
$I_{SC}$	SC Data	$t_p \leq 10\mu\text{s}, V_{GE}=15\text{V}, T_j=125^\circ\text{C}, V_{CC}=900\text{V}, V_{CEM} \leq 1200\text{V}$		675		A

**Diode Characteristics**  $T_C=25^\circ\text{C}$  unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$V_F$	Diode Forward Voltage	$I_C=75\text{A}, V_{GE}=0\text{V}, T_j=25^\circ\text{C}$		1.75	2.20	V
		$I_C=75\text{A}, V_{GE}=0\text{V}, T_j=125^\circ\text{C}$		1.85		
$Q_r$	Recovered Charge	$V_R=600\text{V}, I_F=75\text{A},$ $R_G=7.5\Omega, V_{GE}=-15\text{V}$ $T_j=25^\circ\text{C}$		3.6		$\mu\text{C}$
$I_{RM}$	Peak Reverse Recovery Current			63		A
$E_{rec}$	Reverse Recovery Energy			2.21		mJ
$Q_r$	Recovered Charge			7.9		$\mu\text{C}$
$I_{RM}$	Peak Reverse Recovery Current		$V_R=600\text{V}, I_F=75\text{A},$ $R_G=7.5\Omega, V_{GE}=-15\text{V}$ $T_j=125^\circ\text{C}$		73	
$E_{rec}$	Reverse Recovery Energy			4.48		mJ

**NTC Characteristics**  $T_C=25^\circ\text{C}$  unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$R_{25}$	Rated Resistance			5.0		$\text{k}\Omega$
$\Delta R/R$	Deviation of $R_{100}$	$T_C=100^\circ\text{C}, R_{100}=493.3\Omega$	-5		5	%
$P_{25}$	Power Dissipation				20.0	mW
$B_{25/50}$	B-value	$R_2=R_{25}\exp[B_{25/50}(1/T_2-1/(298.15\text{K}))]$		3375		K

**Module Characteristics**  $T_C=25^\circ\text{C}$  unless otherwise noted

Symbol	Parameter	Min.	Typ.	Max.	Unit
$L_{CE}$	Stray Inductance		21		nH
$R_{CC'+EE'}$	Module Lead Resistance, Terminal to Chip		1.80		$\text{m}\Omega$
$R_{\theta JC}$	Junction-to-Case (per IGBT)			0.225	K/W
	Junction-to-Case (per Diode)			0.370	
$R_{\theta CS}$	Case-to-Sink (per IGBT)		0.193		K/W
	Case-to-Sink (per Diode)		0.317		
$R_{\theta CS}$	Case-to-Sink		0.009		K/W
M	Mounting Torque, Screw M5	3.0		6.0	N.m
G	Weight of Module		300		g




Fig 1. IGBT Output Characteristics




Fig 2. IGBT Transfer Characteristics




Fig 3. IGBT Switching Loss vs.  $I_C$




Fig 4. IGBT Switching Loss vs.  $R_G$




Fig 5. RBSOA




Fig 6. IGBT Transient Thermal Impedance




Fig 7. Diode Forward Characteristics




Fig 8. Diode Switching Loss vs.  $I_F$




Fig 9. Diode Switching Loss vs.  $R_G$




Fig 10. Diode Transient Thermal Impedance






Fig 11. NTC Temperature Characteristic

**Circuit Schematic**



**Package Dimensions**

Dimensions in Millimeters





## Terms and Conditions of Usage

The data contained in this product datasheet is exclusively intended for technically trained staff. you and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application.

This product data sheet is describing the characteristics of this product for which a warranty is granted. Any such warranty is granted exclusively pursuant the terms and conditions of the supply agreement. There will be no guarantee of any kind for the product and its characteristics.

Should you require product information in excess of the data given in this product data sheet or which concerns the specific application of our product, please contact the sales office, which is responsible for you (see [www.powersemi.cc](http://www.powersemi.cc)), For those that are specifically interested we may provide application notes.

Due to technical requirements our product may contain dangerous substances. For information on the types in question please contact the sales office, which is responsible for you.

Should you intend to use the Product in aviation applications, in health or live endangering or life support applications, please notify.

If and to the extent necessary, please forward equivalent notices to your customers.  
Changes of this product data sheet are reserved.