

STARPOWER

SEMICONDUCTOR

IGBT

GD10PJK120L2S


1200V/10A PIM in one-package

General Description

STARPOWER IGBT Power Module provides ultra low conduction loss as well as short circuit ruggedness. They are designed for the applications such as general inverters and UPS.

Features


- Low $V_{CE(sat)}$ NPT IGBT technology
- Low switching losses
- 10 μ s short circuit capability
- $V_{CE(sat)}$ with positive temperature coefficient
- Fast & soft reverse recovery anti-parallel FWD
- Al₂O₃ Substrate for low thermal resistance



Typical Applications

- Inverter for motor drive
- AC and DC servo drive amplifier
- Uninterruptible power supply

Equivalent Circuit Schematic



Absolute Maximum Ratings $T_C=25^{\circ}\text{C}$ unless otherwise noted**IGBT-inverter**

Symbol	Description	Value	Unit
V_{CES}	Collector-Emitter Voltage	1200	V
V_{GES}	Gate-Emitter Voltage	± 20	V
I_C	Collector Current @ $T_C=25^{\circ}\text{C}$	20	A
	@ $T_C=100^{\circ}\text{C}$	10	A
I_{CM}	Pulsed Collector Current $t_p=1\text{ms}$	20	A
P_D	Maximum Power Dissipation @ $T_j=150^{\circ}\text{C}$	93	W

Diode-inverter

Symbol	Description	Value	Unit
V_{RRM}	Repetitive Peak Reverse Voltage	1200	V
I_F	Diode Continuous Forward Current	10	A
I_{FM}	Diode Maximum Forward Current $t_p=1\text{ms}$	20	A

Diode-rectifier

Symbol	Description	Value	Unit
V_{RRM}	Repetitive Peak Reverse Voltage	1600	V
I_O	Average Output Current 50Hz/60Hz,sine wave	10	A
I_{FSM}	Surge Forward Current $V_R=0\text{V}, t_p=10\text{ms}, T_j=45^{\circ}\text{C}$	150	A
I^2t	I^2t -value, $V_R=0\text{V}, t_p=10\text{ms}, T_j=45^{\circ}\text{C}$	110	A^2s

IGBT-brake

Symbol	Description	Value	Unit
V_{CES}	Collector-Emitter Voltage	1200	V
V_{GES}	Gate-Emitter Voltage	± 20	V
I_C	Collector Current @ $T_C=25^{\circ}\text{C}$	20	A
	@ $T_C=100^{\circ}\text{C}$	10	A
I_{CM}	Pulsed Collector Current $t_p=1\text{ms}$	20	A
P_D	Maximum Power Dissipation @ $T_j=150^{\circ}\text{C}$	96	W

Diode-brake

Symbol	Description	Value	Unit
V_{RRM}	Repetitive Peak Reverse Voltage	1200	V
I_F	Diode Continuous Forward Current	10	A
I_{FM}	Diode Maximum Forward Current $t_p=1\text{ms}$	20	A

Module

Symbol	Description	Value	Unit
T_{jmax}	Maximum Junction Temperature	150	$^{\circ}\text{C}$
T_{jop}	Operating Junction Temperature	-40 to +125	$^{\circ}\text{C}$
T_{STG}	Storage Temperature Range	-40 to +125	$^{\circ}\text{C}$
V_{ISO}	Isolation Voltage RMS, $f=50\text{Hz}, t=1\text{min}$	2500	V
F	Mounting Force Per Clamp	20 to 50	N

IGBT-inverter Characteristics $T_C=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit	
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage	$I_C=10A, V_{GE}=15V,$ $T_j=25^\circ\text{C}$		2.45	3.00	V	
		$I_C=10A, V_{GE}=15V,$ $T_j=125^\circ\text{C}$		2.75			
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=125\mu A, V_{CE}=V_{GE},$ $T_j=25^\circ\text{C}$	4.4	5.0	6.0	V	
I_{CES}	Collector Cut-Off Current	$V_{CE}=V_{CES}, V_{GE}=0V,$ $T_j=25^\circ\text{C}$			1.0	mA	
I_{GES}	Gate-Emitter Leakage Current	$V_{GE}=V_{GES}, V_{CE}=0V,$ $T_j=25^\circ\text{C}$			400	nA	
R_{Gint}	Internal Gate Resistance			/		Ω	
C_{ies}	Input Capacitance	$V_{CE}=30V, f=1\text{MHz},$ $V_{GE}=0V$		795		pF	
C_{res}	Reverse Transfer Capacitance				25		pF
Q_G	Gate Charge	$V_{GE}=15V$		48		nC	
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600V, I_C=10A,$ $R_G=100\Omega, V_{GE}=\pm 15V,$ $T_j=25^\circ\text{C}$		172		ns	
t_r	Rise Time			55		ns	
$t_{d(off)}$	Turn-Off Delay Time			189		ns	
t_f	Fall Time			312		ns	
E_{on}	Turn-On Switching Loss				2.34		mJ
E_{off}	Turn-Off Switching Loss				0.74		mJ
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600V, I_C=10A,$ $R_G=100\Omega, V_{GE}=\pm 15V,$ $T_j=125^\circ\text{C}$		176		ns	
t_r	Rise Time			58		ns	
$t_{d(off)}$	Turn-Off Delay Time			199		ns	
t_f	Fall Time			443		ns	
E_{on}	Turn-On Switching Loss				2.71		mJ
E_{off}	Turn-Off Switching Loss				0.98		mJ
I_{SC}	SC Data	$t_p \leq 10\mu s, V_{GE}=15V,$ $T_j=125^\circ\text{C}, V_{CC}=900V,$ $V_{CEM} \leq 1200V$		72		A	

Diode-inverter Characteristics $T_C=25^{\circ}\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V_F	Diode Forward Voltage	$I_C=10\text{A}, V_{GE}=0\text{V}, T_j=25^{\circ}\text{C}$		1.85	2.30	V
		$I_C=10\text{A}, V_{GE}=0\text{V}, T_j=125^{\circ}\text{C}$		2.05		
Q_r	Recovered Charge	$V_R=600\text{V}, I_F=10\text{A},$ $R_G=100\Omega, V_{GE}=-15\text{V}$ $T_j=25^{\circ}\text{C}$		0.98		μC
I_{RM}	Peak Reverse Recovery Current			6.6		A
E_{rec}	Reverse Recovery Energy			0.36		mJ
Q_r	Recovered Charge	$V_R=600\text{V}, I_F=10\text{A},$ $R_G=100\Omega, V_{GE}=-15\text{V}$ $T_j=125^{\circ}\text{C}$		1.51		μC
I_{RM}	Peak Reverse Recovery Current			8.0		A
E_{rec}	Reverse Recovery Energy			0.53		mJ

Diode-rectifier Characteristics $T_C=25^{\circ}\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V_F	Diode Forward Voltage	$I_C=10\text{A}, V_{GE}=0\text{V}, T_j=150^{\circ}\text{C}$		1.00		V
I_R	Reverse Current	$T_j=150^{\circ}\text{C}, V_R=1600\text{V}$			1.0	mA

IGBT-brake Characteristics $T_C=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit	
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage	$I_C=10\text{A}, V_{GE}=15\text{V}, T_j=25^\circ\text{C}$		2.45	3.00	V	
		$I_C=10\text{A}, V_{GE}=15\text{V}, T_j=125^\circ\text{C}$		2.75			
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=125\mu\text{A}, V_{CE}=V_{GE}, T_j=25^\circ\text{C}$	4.4	5.0	6.0	V	
I_{CES}	Collector Cut-Off Current	$V_{CE}=V_{CES}, V_{GE}=0\text{V}, T_j=25^\circ\text{C}$			1.0	mA	
I_{GES}	Gate-Emitter Leakage Current	$V_{GE}=V_{GES}, V_{CE}=0\text{V}, T_j=25^\circ\text{C}$			400	nA	
R_{Gint}	Internal Gate Resistance			/		Ω	
C_{ies}	Input Capacitance	$V_{CE}=30\text{V}, f=1\text{MHz}, V_{GE}=0\text{V}$		795		pF	
C_{res}	Reverse Transfer Capacitance				25		pF
Q_G	Gate Charge	$V_{GE}=15\text{V}$		48		nC	
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600\text{V}, I_C=10\text{A}, R_G=100\Omega, V_{GE}=\pm 15\text{V}, T_j=25^\circ\text{C}$		172		ns	
t_r	Rise Time			55		ns	
$t_{d(off)}$	Turn-Off Delay Time			189		ns	
t_f	Fall Time			312		ns	
E_{on}	Turn-On Switching Loss				2.34		mJ
E_{off}	Turn-Off Switching Loss				0.74		mJ
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600\text{V}, I_C=10\text{A}, R_G=100\Omega, V_{GE}=\pm 15\text{V}, T_j=125^\circ\text{C}$		176		ns	
t_r	Rise Time			58		ns	
$t_{d(off)}$	Turn-Off Delay Time			199		ns	
t_f	Fall Time			443		ns	
E_{on}	Turn-On Switching Loss				2.71		mJ
E_{off}	Turn-Off Switching Loss				0.98		mJ
I_{SC}	SC Data	$t_p \leq 10\mu\text{s}, V_{GE}=15\text{V}, T_j=125^\circ\text{C}, V_{CC}=900\text{V}, V_{CEM} \leq 1200\text{V}$		72		A	

Diode-brake Characteristics $T_C=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V_F	Diode Forward Voltage	$I_C=10\text{A}, V_{GE}=0\text{V}, T_j=25^\circ\text{C}$		1.85	2.30	V
		$I_C=10\text{A}, V_{GE}=0\text{V}, T_j=125^\circ\text{C}$		2.05		
Q_r	Recovered Charge			0.98		μC
I_{RM}	Peak Reverse Recovery Current	$V_R=600\text{V}, I_F=10\text{A},$ $R_G=100\Omega, V_{GE}=-15\text{V}$		6.6		A
E_{rec}	Reverse Recovery Energy	$T_j=25^\circ\text{C}$		0.36		mJ
Q_r	Recovered Charge			1.51		μC
I_{RM}	Peak Reverse Recovery Current	$V_R=600\text{V}, I_F=10\text{A},$ $R_G=100\Omega, V_{GE}=-15\text{V}$		8.0		A
E_{rec}	Reverse Recovery Energy	$T_j=125^\circ\text{C}$		0.53		mJ

NTC Characteristics $T_C=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
R_{25}	Rated Resistance			5.0		k Ω
$\Delta R/R$	Deviation of R_{100}	$T_C=100^\circ\text{C}, R_{100}=493.3\Omega$	-5		5	%
P_{25}	Power Dissipation				20.0	mW
$B_{25/50}$	B-value	$R_2=R_{25}\exp[B_{25/50}(1/T_2-1/(298.15\text{K}))]$		3375		K

Module Characteristics $T_C=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Min.	Typ.	Max.	Unit
L_{CE}	Stray Inductance		30		nH
$R_{CC'+EE'}$ $R_{AA'+CC'}$	Module Lead Resistance, Terminal to Chip @ $T_C=25^\circ\text{C}$		8.00 6.00		m Ω
$R_{\theta JC}$	Junction-to-Case (per IGBT-inverter)			1.338	K/W
	Junction-to-Case (per Diode-inverter)			2.077	
	Junction-to-Case (per Diode-rectifier)			2.094	
	Junction-to-Case (per IGBT-brake-chopper)			1.306	
	Junction-to-Case (per Diode-brake-chopper)			1.955	
$R_{\theta CS}$	Case-to-Sink (per IGBT-inverter)		0.894		K/W
	Case-to-Sink (per Diode-inverter)		1.387		
	Case-to-Sink (per Diode-rectifier)		1.399		
	Case-to-Sink (per IGBT-brake-chopper)		0.872		
	Case-to-Sink (per Diode-brake-chopper)		1.306		
$R_{\theta CS}$	Case-to-Sink		0.058		K/W
G	Weight of Module		24		g




Fig 1. IGBT-inverter Output Characteristics




Fig 2. IGBT-inverter Transfer Characteristics




Fig 3. IGBT-inverter Switching Loss vs. I_C




Fig 4. IGBT-inverter Switching Loss vs. R_G




Fig 5. IGBT-inverter RBSOA




Fig 6. IGBT-inverter Transient Thermal Impedance




Fig 7. Diode-inverter Forward Characteristics




Fig 8. Diode-inverter Switching Loss vs. I_F




Fig 9. Diode-inverter Switching Loss vs. R_G




Fig 10. Diode-inverter Transient Thermal Impedance




Fig 11. Diode-rectifier Forward Characteristics




Fig 12. IGBT-brake Output Characteristics




Fig 13. Diode-brake Forward Characteristics






Fig 14. NTC Temperature Characteristic

Circuit Schematic



Package Dimensions

Dimensions in Millimeters



Terms and Conditions of Usage

The data contained in this product datasheet is exclusively intended for technically trained staff. you and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application.

This product data sheet is describing the characteristics of this product for which a warranty is granted. Any such warranty is granted exclusively pursuant the terms and conditions of the supply agreement. There will be no guarantee of any kind for the product and its characteristics.

Should you require product information in excess of the data given in this product data sheet or which concerns the specific application of our product, please contact the sales office, which is responsible for you (see www.powersemi.cc), For those that are specifically interested we may provide application notes.

Due to technical requirements our product may contain dangerous substances. For information on the types in question please contact the sales office, which is responsible for you.

Should you intend to use the Product in aviation applications, in health or live endangering or life support applications, please notify.

If and to the extent necessary, please forward equivalent notices to your customers.
Changes of this product data sheet are reserved.