

STARPOWER

SEMICONDUCTOR

IGBT

GD900HFA120C6S

1200V/900A 2 in one-package

General Description

STARPOWER IGBT Power Module provides ultra low conduction loss as well as short circuit ruggedness. They are designed for the applications such as hybrid and electric vehicle.


Features

- Low $V_{CE(sat)}$ Trench IGBT technology
- Short circuit capability
- $V_{CE(sat)}$ with positive temperature coefficient
- Maximum junction temperature 175°C
- Low inductance case
- Fast & soft reverse recovery anti-parallel FWD
- Isolated copper baseplate using DBC technology

Typical Applications

- Hybrid and electric vehicle
- Inverter for motor drive
- Uninterruptible power supply

Equivalent Circuit Schematic



Absolute Maximum Ratings $T_C=25^{\circ}\text{C}$ unless otherwise noted**IGBT**

Symbol	Description	Values	Unit
V_{CES}	Collector-Emitter Voltage	1200	V
V_{GES}	Gate-Emitter Voltage	± 20	V
I_C	Collector Current @ $T_C=90^{\circ}\text{C}$	900	A
I_{CM}	Pulsed Collector Current $t_p=1\text{ms}$	1800	A
P_D	Maximum Power Dissipation @ $T_j=175^{\circ}\text{C}$	3409	W

Diode

Symbol	Description	Values	Unit
V_{RRM}	Repetitive Peak Reverse Voltage	1200	V
I_F	Diode Continuous Forward Current	900	A
I_{FM}	Diode Maximum Forward Current $t_p=1\text{ms}$	1800	A
I_{FSM}	Surge Forward Current $t_p=10\text{ms}$ @ $T_j=125^{\circ}\text{C}$ @ $T_j=175^{\circ}\text{C}$	2392	A
		2448	
I^2t	I^2t -value, $t_p=10\text{ms}$ @ $T_j=125^{\circ}\text{C}$ @ $T_j=175^{\circ}\text{C}$	28608	A^2s
		29964	

Module

Symbol	Description	Value	Unit
T_{jmax}	Maximum Junction Temperature	175	$^{\circ}\text{C}$
T_{jop}	Operating Junction Temperature	-40 to +150	$^{\circ}\text{C}$
T_{STG}	Storage Temperature Range	-40 to +125	$^{\circ}\text{C}$
V_{ISO}	Isolation Voltage RMS, $f=50\text{Hz}$, $t=1\text{min}$	4000	V

IGBT Characteristics $T_c=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit	
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage	$I_C=900\text{A}, V_{GE}=15\text{V}, T_j=25^\circ\text{C}$		1.40	1.85	V	
		$I_C=900\text{A}, V_{GE}=15\text{V}, T_j=125^\circ\text{C}$		1.60			
		$I_C=900\text{A}, V_{GE}=15\text{V}, T_j=175^\circ\text{C}$		1.65			
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=24.0\text{mA}, V_{CE}=V_{GE}, T_j=25^\circ\text{C}$	5.5	6.3	7.0	V	
I_{CES}	Collector Cut-Off Current	$V_{CE}=V_{CES}, V_{GE}=0\text{V}, T_j=25^\circ\text{C}$			1.0	mA	
I_{GES}	Gate-Emitter Leakage Current	$V_{GE}=V_{GES}, V_{CE}=0\text{V}, T_j=25^\circ\text{C}$			400	nA	
R_{Gint}	Internal Gate Resistance			0.5		Ω	
C_{ies}	Input Capacitance	$V_{CE}=25\text{V}, f=100\text{kHz}, V_{GE}=0\text{V}$		51.5		nF	
C_{res}	Reverse Transfer Capacitance				0.36		nF
Q_G	Gate Charge	$V_{GE}=-15\dots+15\text{V}$		13.6		μC	
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600\text{V}, I_C=900\text{A}, R_G=0.51\Omega, L_S=40\text{nH}, V_{GE}=-8\text{V}/+15\text{V}, T_j=25^\circ\text{C}$		330		ns	
t_r	Rise Time			140		ns	
$t_{d(off)}$	Turn-Off Delay Time			842		ns	
t_f	Fall Time			84		ns	
E_{on}	Turn-On Switching Loss			122		mJ	
E_{off}	Turn-Off Switching Loss			87.8		mJ	
$t_{d(on)}$	Turn-On Delay Time		$V_{CC}=600\text{V}, I_C=900\text{A}, R_G=0.51\Omega, L_S=40\text{nH}, V_{GE}=-8\text{V}/+15\text{V}, T_j=125^\circ\text{C}$		373		ns
t_r	Rise Time				155		ns
$t_{d(off)}$	Turn-Off Delay Time				915		ns
t_f	Fall Time				135		ns
E_{on}	Turn-On Switching Loss			158		mJ	
E_{off}	Turn-Off Switching Loss			104		mJ	
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600\text{V}, I_C=900\text{A}, R_G=0.51\Omega, L_S=40\text{nH}, V_{GE}=-8\text{V}/+15\text{V}, T_j=175^\circ\text{C}$			390		ns
t_r	Rise Time				172		ns
$t_{d(off)}$	Turn-Off Delay Time				950		ns
t_f	Fall Time				162		ns
E_{on}	Turn-On Switching Loss			178		mJ	
E_{off}	Turn-Off Switching Loss			114		mJ	
I_{SC}	SC Data		$t_p \leq 8\mu\text{s}, V_{GE}=15\text{V}, T_j=150^\circ\text{C}, V_{CC}=800\text{V}, V_{CEM} \leq 1200\text{V}$		3200		A
			$t_p \leq 6\mu\text{s}, V_{GE}=15\text{V}, T_j=175^\circ\text{C}, V_{CC}=800\text{V}, V_{CEM} \leq 1200\text{V}$		3000		A

Diode Characteristics $T_c=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
V_F	Diode Forward Voltage	$I_F=900\text{A}, V_{GE}=0\text{V}, T_j=25^\circ\text{C}$		1.60	2.00	V
		$I_F=900\text{A}, V_{GE}=0\text{V}, T_j=125^\circ\text{C}$		1.60		
		$I_F=900\text{A}, V_{GE}=0\text{V}, T_j=175^\circ\text{C}$		1.50		
Q_r	Recovered Charge			77.4		μC
I_{RM}	Peak Reverse Recovery Current	$V_R=600\text{V}, I_F=900\text{A},$ $-di/dt=4930\text{A}/\mu\text{s}, V_{GE}=-8\text{V},$ $L_S=38\text{nH}, T_j=25^\circ\text{C}$		375		A
E_{rec}	Reverse Recovery Energy			22.3		mJ
Q_r	Recovered Charge			120		μC
I_{RM}	Peak Reverse Recovery Current	$V_R=600\text{V}, I_F=900\text{A},$ $-di/dt=4440\text{A}/\mu\text{s}, V_{GE}=-8\text{V},$ $L_S=38\text{nH}, T_j=125^\circ\text{C}$		419		A
E_{rec}	Reverse Recovery Energy			36.2		mJ
Q_r	Recovered Charge			148		μC
I_{RM}	Peak Reverse Recovery Current	$V_R=600\text{V}, I_F=900\text{A},$ $-di/dt=4160\text{A}/\mu\text{s}, V_{GE}=-8\text{V},$ $L_S=38\text{nH}, T_j=175^\circ\text{C}$		456		A
E_{rec}	Reverse Recovery Energy			44.5		mJ

NTC Characteristics $T_c=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
R_{25}	Rated Resistance			5.0		k Ω
$\Delta R/R$	Deviation of R_{100}	$T_c=100^\circ\text{C}, R_{100}=493.3\Omega$	-5		5	%
P_{25}	Power Dissipation				20.0	mW
$B_{25/50}$	B-value	$R_2=R_{25}\exp[B_{25/50}(1/T_2-1/(298.15\text{K}))]$		3375		K
$B_{25/80}$	B-value	$R_2=R_{25}\exp[B_{25/80}(1/T_2-1/(298.15\text{K}))]$		3411		K
$B_{25/100}$	B-value	$R_2=R_{25}\exp[B_{25/100}(1/T_2-1/(298.15\text{K}))]$		3433		K

Module Characteristics $T_c=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Min.	Typ.	Max.	Unit
L_{CE}	Stray Inductance		20		nH
$R_{CC'+EE'}$	Module Lead Resistance, Terminal to Chip		0.80		m Ω
R_{thJC}	Junction-to-Case (per IGBT)			0.044	K/W
	Junction-to-Case (per Diode)			0.070	
R_{thCH}	Case-to-Heatsink (per IGBT)		0.029		K/W
	Case-to-Heatsink (per Diode)		0.047		
	Case-to-Heatsink (per Module)		0.009		
M	Terminal Connection Torque, Screw M6	3.0		6.0	N.m
	Mounting Torque, Screw M5	3.0		6.0	
G	Weight of Module		350		g




Fig 1. IGBT Output Characteristics




Fig 2. IGBT Transfer Characteristics




Fig 3. IGBT Transfer Characteristics




Fig 4. IGBT Switching Loss vs. I_c




Fig 5. IGBT Switching Loss vs. R_G




Fig 6. RBSOA




Fig 7. IGBT Transient Thermal Impedance




Fig 8. Diode Forward Characteristics




Fig 9. Diode Switching Loss vs. I_F




Fig 10. Diode Switching Loss vs. R_G




Fig 11. Diode Transient Thermal Impedance






Fig12. NTC Temperature Characteristic

Circuit Schematic



Package Dimensions

Dimensions in Millimeters



 = all dimension with a tolerance of ± 0.5

Terms and Conditions of Usage

The data contained in this product datasheet is exclusively intended for technically trained staff. you and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application.

This product data sheet is describing the characteristics of this product for which a warranty is granted. Any such warranty is granted exclusively pursuant the terms and conditions of the supply agreement. There will be no guarantee of any kind for the product and its characteristics.

Should you require product information in excess of the data given in this product data sheet or which concerns the specific application of our product, please contact the sales office, which is responsible for you (see www.powersemi.cc), For those that are specifically interested we may provide application notes.

Due to technical requirements our product may contain dangerous substances. For information on the types in question please contact the sales office, which is responsible for you.

Should you intend to use the Product in aviation applications, in health or live endangering or life support applications, please notify.

If and to the extent necessary, please forward equivalent notices to your customers.
Changes of this product data sheet are reserved.